



AT 200 Copper Anti-Tarnish

DESCRIPTION

AT 200 Copper Anti-Tarnish protects copper and copper alloys from tarnishing by forming a corrosion resistant film on their surface. This film will also protect silver from tarnishing for short periods of time.

The additives in AT 200 Copper Anti-Tarnish will tie up copper ions loosely preventing them from immersion on other metals such as aluminum and steel.

OPERATING PARAMETERS

Concentration	1% by volume
Temperature	Ambient 80-90°F
Time	30-60 Seconds
Equipment	Polypro, PVC or Stainless steel

PHYSICAL PROPERTIES

Appearance	Clear to light brown
Physical State	Liquid
Specific Gravity	1.0
pH	12.0
Flash Point:	Non-Flammable
Shelf Life	180 days

CONTROL PROCEDURES

Make-up: clean tank thoroughly, fill with clean water.
Add 1% by volume **AT 200 Copper Anti-Tarnish**.

Usually, protection will prevent tarnishing 24-36 hours. Small additions can be made of the **Anti-Tarnish** extending the bath life.

ANALYSIS

Analysis is not required to use this product.



SAFETY AND STORAGE

Avoid eye, skin and clothing contact. In case of skin contact, wash skin immediately with soap and water. If clothes or shoes are contaminated, remove and wash before reuse. Seek medical treatment if ill or irritation develops. Eye contact, wash with running water 15 minutes. Seek medical attention.

Store in original container. Keep container closed at all times. Do not store in direct sunlight or high temperature area and keep away from ignition sources. Avoid strong oxidizing agents and acid. Be cautious when handling this product.

WASTE TREATMENT

Contact your FCT Water representative for waste treatment recommendations.

MISCELLANEOUS

Packaging: 5 gallon container, 55 gallon drum and 275 gallon tote.